

Bucky Grey Back, Non-curl Rollup Banner – Data Sheet

Specially design for roll-up banner displays. It was specially formulated to avoid curling of the edges. The surface is smooth with a special PVC coating for incredible dot gain for high resolution printing.



General

Front Color	Back Color	Packing	Weight oz/yd ²	Weight gr/mt ²	Finish	Roll Length
White	Grey	Carton tube	13	440	Satin	33 yd (100 feet)

Available Width

English (Inch)	38
Metric (cm)	96

Application

Front-Lit	Back-Lit	Banner	Billboard	Block out	Awning	Truck Curtain
*		*		*		

Compatibility

Eco-Solvent	Solvent	UV-LED	UV	Latex	Screen P	Dye Sub
*	*	*	*	*	*	

Physical Properties - Double Sided Rollup Banner

Type	Values	Standard
Base:	Polyethylene Terephthalate	
Thickness	145 micron	
Coating:	PVC	
Total Weight(g/sqm):	440±15g (13.2 Oz)	
Tensile Strength(L):	1182N/5cm	DIN53352
Tensile Strength(W):	1173N/5cm	DIN53354
Tearing Strength(L):	34N/5cm	DIN53354
Tearing Strength(L):	27N/5cm	DIN53363
Peeling Strength(L):	can't peeling	DIN53363
Peeling Strength(W): can't peeling	DIN53363	DIN53363
Temperature		-30~70°C

Storage (shelf life)	2 years (Excess temperature and humidity will shorten stability and shelf life)
Outdoor durability	3 months (physical properties of the material) Printing durability will depend on printing technology, inks, application and handling

Statement: All technical information herein is based on private tests and does not warrant or guarantee the accuracy or completeness of this information. Printing quality, color matching and adhesion may vary on different printing systems. For special applications independent testing would be recommended. For more information visit www.iohda.com